



SUPER KOTE 5000[®]

ACRYLIC LATEX ENAMEL

SATIN FINISH 1160

Features

- Premium commercial acrylic latex designed for the professional painter
- No spatter and good flow & leveling provide fast production
- Professional satin finish withstands washing and scrubbing
- Low odor and soap and water cleanup

General Description

Super Kote 5000[®] Acrylic Satin Enamel is suited for wall and trim applications in kitchens, bathrooms, family rooms, hallways and bedrooms where routine cleaning is needed. Fast dry, low odor and a pleasant satin sheen make it an ideal finish for residential or commercial jobs.

Recommended For

Interior drywall, plaster, wood, metal, masonry and stucco in commercial, institutional and residential applications. Ideal for wall and trim where routine cleaning is needed. Also suitable for exterior, vertical concrete or stucco surfaces in southern climates where freezing temperatures are rare.

Limitations

- May be applied when surface and air temperatures are between 40 °F and 90 °F (4.4 °C and 32.2 °C).

Product Information

Colors — Standard:	Technical Data◇	White
White	Vehicle Type	Vinyl Acrylic
	Pigment Type	Titanium Dioxide
	Volume Solids	31 ± 1.0%
— Tint Bases:	Coverage per Gallon at Recommended Film Thickness	300 – 400 Sq. Ft.
1160-32, Pastel Base	Recommended Film Thickness – Wet	4 to 5.3 mils
1160-33, Tint Base	– Dry	1.4 to 1.6 mils
1160-34, Deep Base	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
1160-36, Accent Base	Dry Time @ 77°F – Tack Free	30 Minutes
	(25°C) @ 50% RH – To Recoat	4 Hours
— Special Colors:	High humidity and cool temperatures will result in longer dry, recoat and service times.	
Contact your dealer.	Dries By	Evaporation
	Viscosity	90 – 95 KU
Certification:	Flash Point	N/A
The products supported by this data sheet contain a maximum of 100 grams per liter VOC / VOS (0.83 lbs/gal.) excluding water & exempt solvents	Gloss / Sheen	Satin
This product is compliant under the Ozone Transport Commission regulations as a Non-Flat Coating.	Surface Temperature – Min.	40°F
	at Application – Max.	90°F
This product is certified under MPI #43. This product does meet qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.	Thin With	Clean Water
	Clean Up Thinner	Warm Soapy Water
Technical Assistance:	Weight Per Gallon	10.6 lbs
Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-225-5554, see www.coronadopaint.com or consult your local Yellow Pages.	Storage Temperature – Min.	40 °F
	– Max.	90 °F
	Volatiles Organic Compounds (VOC)	
	95 Grams/Liter	.79 Lbs./Gallon

◇ Reported values are for White. Contact dealer for values of other bases or colors.

Super Kote 5000[®] Acrylic Latex Satin Enamel 1160 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

Difficult Substrates: Insl-x[®] offers a variety of specialty primers for use over difficult substrates such as plaster, bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your dealer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary.

Wood and Engineered Wood Products:

Primer: All-Purpose Interior Alkyd Primer (Insl-x[®] Prime Lock™ Plus) or All-Purpose Interior Acrylic Primer (Super Kote 5000[®] 40-11)

Finish: 1 or 2 coats of Super Kote 5000[®] Acrylic Latex Enamel Satin (1160 Line)

Bleeding Type Woods, (Redwood and Cedar):

Primer: All-Purpose Interior Alkyd Primer (Insl-x[®] Prime Lock™ Plus)

Finish: 1 or 2 coats of Super Kote 5000 Acrylic Latex Enamel Satin (1160 Line)

Drywall:

Primer: All-Purpose Interior Acrylic Primer (Super Kote 5000[®] 40-11)

Finish: 1 or 2 coats of Super Kote 5000[®] Acrylic Latex Enamel Satin (1160 Line)

Plaster:

Primer: All-Purpose Interior Acrylic Primer (Super Kote 5000[®] 40-11)

Finish: 1 or 2 coats of Super Kote 5000[®] Acrylic Latex Enamel Satin (1160 Line)

Masonry; Rough or Pitted Masonry:

Primer: Masonry Latex Block Filler (Super Kote 5000[®] 958)

Finish: 1 or 2 coats of Super Kote 5000[®] Acrylic Latex Enamel Satin (1160 Line)

Masonry; Smooth Poured or Pre-cast Concrete:

Primer: All-Purpose Interior Acrylic Primer (Super Kote 5000[®] 40-11)

Finish: 1 or 2 coats of Super Kote 5000[®] Acrylic Latex Enamel Satin (1160 Line)

Ferrous Metal (steel & iron):

Primer: Acrylic Metal Primer (Rust Scat[®] 36) or Alkyd Metal Primer (Rust Scat[®] 35)

Finish: 1 or 2 coats of Super Kote 5000[®] Acrylic Latex Satin Finish (1160 Line)

Hard glossy alkyd surfaces: Abrasion by sanding leads to optimum adhesion.

Non-Ferrous Metal (galvanized & aluminum): All new metal surfaces must be thoroughly cleaned with an Oil & Grease Emulsifier to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion
Primer: Acrylic Metal Primer (Rust Scat[®] 36)

Finish: 1 or 2 coats of Super Kote 5000[®] Acrylic Latex Satin (1160)

Repaint, All Substrates: Prime bare areas with the primer recommended for the substrate above.

Application

Stir product with a circular, lifting motion before you begin to paint. Super Kote 5000[®] Acrylic Latex Satin Enamel may be applied by brush, roller, pad or spray techniques, at a rate of application not to exceed 400 square feet per gallon. Surface texture and porosity will affect actual yield. **For best brush application** results, use a quality synthetic filament brush. **For roller application**, use a ¼" to 3/8" nap cover for smooth surfaces, a ½" nap cover for semi-rough surfaces and a ¾" – 1" nap cover for rough surfaces. Do not jeopardize the success of your painting project by using poor quality applicator tools. Apply only when surface and air temperatures are between 50° and 90° F.

Airless – Tip size and atomization pressures will vary with the type of equipment, viscosity and temperature. An orifice of .017 - .019 will provide the most satisfactory spray pattern. Super Kote 5000[®] Acrylic Latex Satin Enamel may be thinned with clean water, up to 15%, for spray application.

Cleanup

Clean up with warm, soapy water followed by a clean water rinse.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental, Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Cleanup".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Material Safety Data Sheet for
additional health and safety information.**